

800kVA B.E.S.T - Aluminium Wound Amorphous Core Mineral Oil Filled Distribution Transformer

Specification IEC 60076

Part Number 800STDALT3ACO

Rated Power, Sr 800 kVA

Rated Frequency, fr 50 Hz

Rated High Voltage, Ur 11000 v

HV Tapping Range +71/2, -5%

Tap Switch, CFVV Off Circuit

Tap Steps 5 x 21/2 %

Rated Low Voltage, Ur 415 v

Cooling Method ONAN

Thermal Class A (105°)

Location Indoor/Outdoor

Coolant Mineral Oil

Insulation Level Li75.Ac28 / Ac3

Vector Group Dyn11

Core Material Amorphous

Winding Material Aluminium

Temperature Rise Oil/Wdg 60 / 65 °

Load Loss @ 75°C 4,880 w

No Load Loss 345 w

Tier 2 EU 548/2014 Ak Ao -10%

Impedance 4.75%

HV Cable Box

3 pole single gland air filled, shroud insulated, suitable for a single multi core cable from below complete with a mild steel gland plate. Compliant with BS EN 50336 and BS 2562.

(Excludes necessary glands, lugs and termination kit).

LV Cable Box

4 -pole 4 gland air insulated, suitable for single core cables from below, complete with mono block bushing, non-magnetic gland plate. Compliant with BS EN 50336 and BS 2562.

(Excludes necessary cables, glands and lugs).

Paint Finish

Painted in accordance with our standard system with a dark admiralty grey finish to BS381C – 632 incorporating corrosion category C4 of ISO 12944.

Neutral Point

A fully rated neutral point provided as standard.

Standard Fittings

ENA TS 35-1 terminal height

Oil filler top plate

Oil level indicator

Main lifters

Breather Pipe

Thermometer pocket

Rating and diagram plate with CE and UKCA marks

Oil drain / sampling valve

Stainless steel earth lugs

Jacking points

Skid under base

Standard Accessories Supplied Loose

1 x Desiccant breather

 $2 \times Tins$ touch up paint (1x Grey, 1x Yellow)

1 x Paint Brush

1 x Transformer routine test certificate

1 x Certificate of Conformity

1 x O&M manual

For standard definitions and references please refer to the latest edition of BS EN 60076-1.

Bowers Electricals Ltd, Heanor Gate Road, Heanor, Derbyshire DE75 7GX

Telephone: 01773 531531 (24 hours)

Fax: 01773 716171

E-mail: enquiries@bowerselec.co.uk

www.bowerselec.co.uk

Registered at the above address in England Company No: 1955004 VAT Ref: 4163613